



AMERICAN
HAULER

HAULING THE AMERICAN SPIRIT

PREMIUM CARGO TRAILERS THE FALCON



ROBUST, RELIABLE & DOWN TO BUSINESS

Tough jobs. You know, the ones that other trailers shy away from. Not the rugged **FALCON**. It was designed from the ground up for the tough jobs. The heart of the **FALCON** is the steel tube frame with 16" on-center crossmembers, vertical posts, and roof bows. The rugged Armaguard coating on the A-Frame acts like a shield against road hazards. The smooth, screwless exterior makes a perfect backdrop for your company logo. If you're looking for it all — the **FALCON** is your go-to trailer.

SPECIFICATIONS

| | AFX58SA | AFX610SA2 | AFX612SA | AFX714TA2 | AFX716TA2 |
|---|---------------------------|---------------------|---------------------|---------------------|---------------------|
| Body (L x W) | 8'9" x 5'0" | 10'9" x 6'0" | 12'9" x 6'0" | 14'9" x 7'0" | 16'9" x 7'0" |
| Overall (L x W x H) | 11'6" x 6'8" x 7'4" | 14'0" x 7'8" x 8'3" | 16'0" x 7'8" x 8'3" | 17'8" x 8'6" x 8'4" | 19'8" x 8'6" x 8'4" |
| Interior (L x W x H) | 8'5" x 4'8" x 5'6" | 10'5" x 5'8" x 6'6" | 12'5" x 5'8" x 6'6" | 14'5" x 6'8" x 6'6" | 16'5" x 6'8" x 6'6" |
| Platform Height | 18" | 18" | 18" | 19" | 19" |
| Side Door | N/A | 36" Flush Lock | 36" Flush Lock | 36" Flush Lock | 36" Flush Lock |
| Rear Door W x H | Single Swing 51" x 59" | Ramp 63" x 73" | Ramp 63" x 73" | Ramp 75" x 73" | Ramp 75" x 73" |
| Axle Quantity | Single | Single | Single | Tandem | Tandem |
| Brakes with Breakaway Kit | N/A | Optional | Optional | Electric | Electric |
| Radial Tire Size Tire Load Range | ST205/75R15 C | ST205/75R15 C | ST205/75R15 C | ST205/75R15 C | ST205/75R15 C |
| Hitch Ball Size | 2" | 2" | 2" | 2-5/16" | 2-5/16" |
| Hitch Height to Top of Ball | 16" | 16" | 16" | 17" | 17" |
| Hitch Weight (% of curb weight) | 10-15% | 10-15% | 10-15% | 10-15% | 10-15% |
| GVWR | 2,990 lbs. | 2,990 lbs. | 2,990 lbs. | 7,000 lbs. | 7,000 lbs. |
| Curb Weight (Approx.) | 880 lbs. | 1,100 | 1,250 lbs. | 1,975 lbs. | 2,140 lbs. |
| Payload Capacity (Approx.) | 2,110 lbs. | 1,890 lbs. | 1,740 lbs. | 5,025 lbs. | 4,860 lbs. |
| Tube Main Rails | 2" x 3" Tube | 2" x 3" Tube | 2" x 3" Tube | 2" x 4" Tube | 2" x 4" Tube |
| 12v Connector | 4-Way | 4-Way | 4-Way | 7-Way | 7-Way |

STANDARD FEATURES

- Radius Roof with Radius Front
- .080 Extruded Aluminum Roof Cove
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
(Tandem Axle Models Only)
- Entire Chassis Undercoated
- Armaguard on A-Frame and Rear End Rail
- Ball Coupler Hitch
- Safety Chains to D.O.T Standards
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Radius Fenders
- 1-Piece Seamless Aluminum Roof
- .030 Aluminum Bonded Screwless Exterior (9 colors)
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist and Ramp Extension
(Single Swing Door on 5x8 Model)
- 36" Side Door with Flush Lock
(No Side Door on 5x8 Model)
- 12v LED Exterior Lighting & Slim Line Tail Lights
- 12v LED Dome Lights (2) with Wall Switch
- 3/4" PlexCore Interior Floor
- 3/8" PlexCore Sidewall Liner
- 5000 lb. Floor Mounted D-Rings (4)
- 3-Year Limited Warranty



7' x 16' Falcon with optional Multi-Color Exterior



7' x 16' Falcon with standard ramp door & 3/8" Interior

